



## Portable Hardness Tester



### Advantages

- Wide measuring range. It can measure the hardness of all metallic materials. Direct display of hardness scales HRB, HRC, HV, HB, HS, HL and three types of strength values immediately.
- Large screen LCD, showing all functions and parameters. With EL background light.
- Seven impact devices are available for special application. Automatically identify the type of impact devices, and with the user calibration function.
- Test at any angle, even upside down.
- Large memory could store 100 groups (Relative to average times 32 ~ 1 ) information including single measured value, mean value, impact direction, impact times, material and hardness scale etc.
- Battery information showing the rest capacity of the battery and the charge status.
- Original imported high speed thermal printer support the immediate printing function.
- It can save data permanently.
- NI-MH rechargeable battery as the power source. Charge circuit integrated inside the instrument. Continuous working period of no less than 150 hours (EL off and no printing).
- Auto power off to save energy.
- Excellent after-sale service system for high quality products--two years' warranty. Easy to buy and comfortable to use.

### Main Application

- Die cavity of molds
- Bearings and other parts
- Failure analysis of pressure vessel, steam generator and other equipment
- Heavy work piece
- The installed machinery and permanently assembled parts
- Testing surface of a small hollow space
- Material identification in the warehouse of metallic materials
- Rapid testing in large range and multi-measuring areas for large-scale work piece

## Technical Specifications

- Error and repeatability of displayed value:

No.	Type of impact device	Hardness value of Leeb standard hardness block	Error of displayed value	Repeatability
1	D	760±30HLD 530±40HLD	±6 HLD ±10 HLD	6 HLD 10 HLD
2	DC	760±30HLDC 530±40HLDC	±6 HLDC ±10 HLDC	6 HLD 10 HLD
3	DL	878±30HLDL 736±40HLDL	±12 HLDL	12 HLDL
4	D+15	766±30HLD+15 544±40HLD+15	±12 HLD+15	12 HLD+15
5	G	590±40HLG 500±40HLG	±12 HLG	12 HLG
6	E	725±30HLE 508±40HLE	±12 HLE	12 HLE
7	C	822±30HLC 590±40HLC	±12 HLC	12 HLC

- Measuring range : HLD ( 170 ~ 960 ) HLD
- Measuring direction : 0°~360°
- Hardness Scale : HL、HB、HRB、HRC、HRA、HV、HS
- Display : segment LCD
- Data memory : 100 groups max. ( relative to impact times 32 ~ 1 )
- Printing paper: width is ( 57.5±0.5 ) mm, diameter is 30mm.
- Battery pack: 6V NI-MH
- Battery charger: 9V/500mA
- Continuous working period : about 150 hours ( With backlight off, no printing )
- Communication interface : USB1.1
- Outline dimensions : 212mm×80mm×32mm

## Configuration

	No.	Item	Quantity	Remarks
Standard Configuration	1	Main unit	1	
	2	D type impact device	1	With cable
	3	Standard test block	1	
	4	Cleaning brush (I)	1	
	5	Small support ring	1	
	6	Battery Charger	1	9V 500mA
	7	Paper for printing	1	
	8	Manual	1	
	9	Instrument package case	1	
Optional Configuration	11	Cleaning brush (II)	1	For use with G type impact device
	12	Other type of impact devices and support rings		Refer to Table 3 and Table 4 in the appendix.
	13	DataPro software	1	
	14	Communication cable	1	
	15			
	16			

---

For more details contact -

**VERTEX ENGINEERS & ASSOCIATES**

S – 250, Sector – 4,

Airoli, Navi Mumbai – 400 708.

Tel : +91 -22 - 27691675 / 65169832

Email : [info@vertexmachines.com](mailto:info@vertexmachines.com), Visit us at - [www.vertexmachines.com](http://www.vertexmachines.com)